


# Copper Long Barrel 2 Hole Compression Lugs



- ▶ High Conductivity Seamless Copper
- ▶ Electro-Tin Plating Resists Corrosion, reduces contact resistance for Maximum Conductivity
- ▶ Dual Mounting Holes
- ▶ Long Barrel Accommodates Multiple Crimps
- ▶ Color Coded Die Index and Crimp Marks Printed on Barrel
- ▶ UL 486A Listed for Applications Thru 35KV



Dimensions = Inches

Cat. No.	Wire Range	Stud Size	Hole Spacing	Color	A	A1	B	C	D	E	F	G	Box Qty
94310	8 Str.	#10	5/8	Red	2.19	.81	.42	.08	.21	.28	1.26	.63	45
94312	8 Str.	1/4	5/8	Red	2.19	.81	.42	.08	.21	.28	1.26	.63	45
94314	8 Str.	3/8	1	Red	2.18	.80	.42	.08	.41	.38	1.81	1.00	45
94315	6 Str.	1/4	1/2	Blue	2.24	.98	.42	.08	.25	.28	1.14	.50	35
94316	6 Str.	1/4	5/8	Blue	2.36	.98	.42	.08	.25	.28	1.26	.63	35
94317	6 Str.	1/4	3/4	Blue	2.48	.98	.42	.08	.25	.28	1.38	.75	35
94319	6 Str.	3/8	1	Blue	2.91	.98	.42	.08	.41	.38	1.81	1.00	35
94320	6 Str.	1/2	1-3/4	Blue	4.09	.98	.87	.12	.51	.62	2.99	1.75	35
94323	4 Str.	1/4	3/4	Gray	2.52	.98	.49	.09	.25	.28	1.38	.75	25
94324	4 Str.	1/4	5/8	Gray	2.36	.98	.49	.09	.25	.28	1.26	.63	25
94325	4 Str.	5/16	1	Gray	2.51	.98	.49	.09	.33	.32	1.61	1.00	30
94327	4 Str.	3/8	1	Gray	2.95	.98	.49	.09	.41	.38	1.81	1.00	30
94326	4 Str.	1/2	1 3/4	Gray	4.09	.98	.87	.12	.51	.62	2.99	1.75	30
94328	2 Str.	1/4	5/8	Brown	2.52	1.10	.60	.10	.25	.28	1.26	.63	30
94329	2 Str.	1/4	3/4	Brown	2.64	1.10	.60	.10	.25	.28	1.38	.75	30
94330	2 Str.	5/16	3/4	Brown	2.87	1.10	.60	.10	.33	.32	1.61	.75	30
94332	2 Str.	5/16	7/8	Brown	2.87	1.10	.60	.10	.33	.32	1.61	.87	20
94333	2 Str.	3/8	1	Brown	3.07	1.10	.60	.10	.41	.38	1.81	1.00	20
94334	2 Str.	1/2	1 3/4	Brown	4.25	1.10	.81	.10	.51	.62	2.99	1.75	20
94338	1 Str.	1/4	5/8	Green	2.56	1.10	.67	.11	.25	.28	1.26	.63	15
94339	1 Str.	1/4	3/4	Green	2.68	1.10	.67	.11	.25	.28	1.38	.75	15
94340	1 Str.	5/16	7/8	Green	2.67	1.10	.67	.11	.33	.32	1.62	.87	30
94341	1 Str.	3/8	7/8	Green	2.93	1.10	.67	.11	.33	.32	1.61	.87	30
94343	1 Str.	3/8	1	Green	3.07	1.10	.67	.11	.41	.38	1.81	1.00	30
94342	1 Str.	1/2	1 3/4	Green	4.29	1.10	.75	.10	.51	.62	2.99	1.75	30
94345	1/0 Str.	1/4	5/8	Pink	3.20	1.20	.74	.13	.25	.28	1.26	.63	25
94346	1/0 Str.	5/16	7/8	Pink	3.01	1.20	.74	.13	.33	.32	1.61	.87	25
94348	1/0 Str.	3/8	1	Pink	3.21	1.20	.74	.13	.41	.38	1.81	1.00	25
94350	1/0 Str.	1/2	1 3/4	Pink	4.63	1.20	.74	.12	.51	.62	2.99	1.75	25
94352	2/0 Str.	1/4	5/8	Black	2.99	1.37	.81	.12	.25	.28	1.26	.63	20
94353	2/0 Str.	1/4	3/4	Black	2.99	1.38	.81	.12	.25	.28	1.38	.75	20
94354	2/0 Str.	3/8	1	Black	3.43	1.38	.81	.12	.41	.38	1.81	1.00	20
94356	2/0 Str.	1/2	1 3/4	Black	4.61	1.38	.81	.12	.51	.62	2.99	1.75	20
94358	3/0 Str.	1/4	3/4	Orange	3.50	1.37	.90	.13	.25	.28	1.38	.75	15
94359	3/0 Str.	5/16	1	Orange	3.50	1.38	.90	.13	.33	.32	1.81	1.00	15
94360	3/0 Str.	3/8	1	Orange	3.50	1.38	.90	.13	.41	.38	1.81	1.00	15
94361	3/0 Str.	3/8	1-3/4	Orange	4.65	1.38	.90	.13	.41	.38	2.99	1.75	20
94362	3/0 Str.	1/2	1 3/4	Orange	4.65	1.38	.90	.13	.51	.62	2.99	1.75	20
94364	4/0 Str.	1/4	3/4	Purple	3.54	1.42	1.00	.13	.25	.28	1.38	.75	12
94366	4/0 Str.	3/8	1	Purple	3.54	1.42	1.00	.13	.41	.38	1.81	1.00	12
94367	4/0 Str.	3/8	1-3/4	Purple	3.54	1.42	1.00	.13	.41	.38	2.99	1.75	20
94368	4/0 Str.	1/2	1 3/4	Purple	4.72	1.42	1.00	.13	.51	.62	2.99	1.75	20
94372	250 MCM	3/8	1	Yellow	3.78	1.61	1.09	.15	.41	.38	1.81	1.00	12
94374	250 MCM	1/2	1 3/4	Yellow	4.96	1.61	1.09	.15	.51	.62	2.99	1.75	15
94377	300 MCM	3/8	1	White	5.31	1.96	1.19	.15	.41	.38	1.81	1.00	12
94378	300 MCM	1/2	1 3/4	White	5.31	1.97	1.19	.15	.51	.62	2.99	1.75	12
94381	350 MCM	3/8	1	Red	4.21	1.97	1.28	.17	.51	.38	1.81	1.00	10
94382	350 MCM	1/2	1 3/4	Red	5.39	1.97	1.28	.17	.51	.62	2.99	1.75	10
94385	400 MCM	3/8	1	Blue	5.47	1.97	1.39	.18	.41	.38	1.81	1.00	10
94386	400 MCM	1/2	1 3/4	Blue	5.47	1.97	1.39	.18	.51	.62	2.99	1.75	10
94389	500 MCM	3/8	1	Brown	4.57	2.24	1.54	.22	.41	.38	1.81	1.00	8
94390	500 MCM	1/2	1 3/4	Brown	5.75	2.24	1.54	.22	.51	.62	2.99	1.75	8
94393	600 MCM	3/8	1	Green	4.61	2.24	1.72	.25	.41	.38	1.81	1.00	6
94394	600 MCM	1/2	1 3/4	Green	5.79	2.24	1.72	.25	.51	.62	2.99	1.75	6
94397	750 MCM	3/8	1	Black	5.12	2.64	1.90	.27	.41	.38	1.81	1.00	4
94398	750 MCM	1/2	1 3/4	Black	6.30	2.64	1.90	.27	.51	.62	2.99	1.75	4
94399	1000 MCM	1/2	1 3/4	White	7.125	3.16	2.16	.34	.51	.62	3.06	1.75	1

**Compression Power Connectors**

**B6**