



**Wallpack • Floodlight • Area Light  
Perimeter & Security Light**



**LED  
Lighting**

**CC2**

**SPECIFICATIONS**

- ▶ Phillips LUMILED LUXEON 3030 LEDs
- ▶ TOWIN or Inventronics Driver
- ▶ Integral Cooling Fin Releases Heat Efficiently to Maintain the Life of LEDs & LED Driver
- ▶ Corrosion Resistant Die Cast Aluminum Housing
- ▶ Polycarbonate Lens
- ▶ Superior Architectural Powder Coat Finish
- ▶ Stainless Steel Hardware
- ▶ Photocontrol can be installed remotely
- ▶ 50,000+ Hour Life Expectancy
- ▶ Voltage: 120/208/240/277VAC
- ▶ Color Temperature: 3000K & 5000K
- ▶ CRI: 81+
- ▶ Power Factor: .9 - .97
- ▶ Light Pattern: Type II, 7H X 7V, 120° V X 90° H
- ▶ Operating Temperature: -40°F To 131°F
- ▶ IP65 Rated (NEMA 4X) Dust & Water Tight
- ▶ cULus Listed for Wet Locations
- ▶ DLC Listed
- ▶ 5 Year Warranty

**FLEXIBLE MOUNTING**

<b>Bracket</b>	<b>15W – 50W</b>
<b>1/2" Knuckle</b>	<b>15W – 50W</b>
<b>Wall Mount</b>	<b>30W – 150W</b>
<b>Trunion Mount</b>	<b>80W – 300W</b>
<b>Slipfitter Mount</b>	<b>80W - 300W</b>
<b>Pole Mount</b>	<b>80W – 300W</b>



**\*All 100W thru 300W FlatPanel Series  
Fixtures are Dimmable**