

Dusk To Dawn LED Series

NEW!



71333
Available
October 2016



Lower Pricing



cUL US LISTED

71330


LED Lighting




71332

All Models Include Premium 105-285V Surge Protected Locking Photocell

DLC LISTED



71330



71332/71333

- ▶ Phillips LUMILED LUXEON 3030 LEDs
- ▶ TOWIN Driver
- ▶ All Models Include Morris #39052 Surge Protected 110-277V Twist-Lock Photocell
- ▶ Integral Cooling Fin Releases the Heat Efficiently to Maintain the Life of LEDs & LED Driver
- ▶ Corrosion Resistant Die Cast Aluminum Housing
- ▶ Anti-Glare Polycarbonate Frosted Lens
- ▶ Superior Powder Coat Finish
- ▶ Stainless Steel Hardware
- ▶ Voltage: 120/208/240/277VAC
- ▶ Color Temperature: 5000K Cool White
- ▶ CRI: 83
- ▶ Power Factor: .98 @ 120V .91 @ 277V
- ▶ Input Current: .41A @ 120V .49A @ 277V
- ▶ Light Pattern: 134° Beam Angle
- ▶ Operation Temperature: -40°F to 131°F
- ▶ 50,000+ Hour LED Life Expectancy
- ▶ *71332 & 71333 Include Optional Use 21" 90° Mounting Arm
- ▶ IP65 (NEMA 4X) Dust & Water Tight
- ▶ cULus listed for Wet Locations
- ▶ DLC Listed - 71332 only (71330 & 71333 is not DLC Listed)
- ▶ 5 Year Warranty

CC7

Cat. No.	Mounting	Watts	Delivered Lumens	Replaces Metal Halide	DLC	Dimensions (Inches)							Weight (Lbs)	Case Qty
						A	B	C	D	E	F	G		
71330	Wall	42.2	2167	100W	No	14	10	7	-	-	-	-	6.3	6
71332*	Bracket	48	5342	150W	Yes	13-1/2	10	7-1/8	22-7/16	18-5/8	1-5/8	9	7.5	2
71333*	Bracket	50	5,026	150W	No	13-1/2	9-1/2	7	24	21-1/4	1-5/8	9	7.5	2

*Mounting Arm Included


Array-Flood LED Series



71312
Full Bracket



71313
1/2" Adjustable Knuckle



cUL US LISTED

- ▶ Cree XTE LEDs
- ▶ Integral Cooling Fin Releases Heat Efficiently to Maintain the Life of LEDs & LED Driver
- ▶ Corrosion Resistant Die Cast Aluminum Housing
- ▶ Tempered Glass Lens
- ▶ Anodized Aluminum Reflector
- ▶ Superior Architectural Bronze Powder Coat Finish
- ▶ Stainless Steel Hardware
- ▶ Photocell not included (can be installed on fixture)
- ▶ 60,000+ Hour LED Life Expectancy

- ▶ Voltage: 120/208/240/277VAC
- ▶ Color Temperature: 4700K Cool White
- ▶ CRI: 72+
- ▶ Light Pattern: 120° Beam Angle
- ▶ Operation Temperature: -22°F to 104°F
- ▶ Weight: 7.1 Lbs
- ▶ IP65 (NEMA 4X) Dust & Water Tight
- ▶ cULus Listed for Wet Locations
- ▶ 5 Year Warranty

Cat. No.	Mounting	Watts	Delivered Lumens	Replaces Metal Halide	Number of LEDs	Dimensions (Inches)					Case Qty
						A	B	C	D	E	
71312	Full Bracket	47	3628	100W	20	7"	10"	1-7/8"	1-7/8"	2-3/4"	6
71313	1/2" Adj. Knuckle	47	3628	100W	20	7"	10"	1-7/8"	2-3/4"	2-3/4"	6