



- ▶ Flexible Polyolefin Heat Shrink Tubing
- ▶ 2:1 Shrink Ratio
- ▶ 600 Volt
- ▶ 257°F (125°C) Continuous Operation
- ▶ For Insulating, Wire Harness, Wire Bundling, Splicing & Terminations
- ▶ UL 224 Recognized

Dimensions = Inches

Cat No.	Length	Color	Diameter Before Shrinking	Diameter After Shrinking	Bag Qty
68030	6"	Black	.078	.029	50
68032	6"	Black	.098	.039	50
68034	6"	Black	.137	.059	50
68036	6"	Black	.211	.098	10
68038	6"	Black	.250	.117	10
68040	6"	Black	.367	.176	10
68042	6"	Black	.484	.234	10
68044	6"	Black	.827	.390	10
68046	6"	Black	1.26	.590	10
68322	6"	Clear	.078	.029	50
68323	6"	Clear	.098	.039	50
68324	6"	Clear	.137	.059	50
68325	6"	Clear	.211	.098	10
68326	6"	Clear	.250	.117	10
68327	6"	Clear	.367	.176	10
68328	6"	Clear	.484	.234	10
68329	6"	Clear	.827	.390	10
68331	6"	Red	.078	.029	50
68332	6"	Red	.098	.039	50
68333	6"	Red	.137	.059	50
68334	6"	Red	.211	.098	10
68335	6"	Red	.250	.117	10
68336	6"	Red	.367	.176	10
68337	6"	Red	.484	.234	10
68338	6"	Red	.827	.390	10
68339	6"	Red	1.26	.590	10
68340	6"	Green	.078	.029	50
68341	6"	Green	.098	.039	50
68342	6"	Green	.137	.059	50
68343	6"	Green	.211	.098	10
68344	6"	Green	.250	.117	10
68345	6"	Green	.367	.176	10
68346	6"	Green	.484	.234	10
68347	6"	Green	.827	.390	10
68348	6"	Green	1.26	.590	10
68349	6"	White	.078	.029	50
68350	6"	White	.098	.039	50
68351	6"	White	.137	.059	50
68352	6"	White	.211	.098	10
68353	6"	White	.250	.117	10
68354	6"	White	.367	.176	10
68355	6"	White	.484	.234	10
68356	6"	White	.827	.390	10
68357	6"	White	1.26	.590	10
68358	6"	Blue	.078	.029	50
68359	6"	Blue	.098	.039	50
68360	6"	Blue	.137	.059	50
68361	6"	Blue	.211	.098	10
68362	6"	Blue	.250	.117	10
68363	6"	Blue	.367	.176	10
68364	6"	Blue	.484	.234	10
68365	6"	Blue	.827	.390	10
68366	6"	Blue	1.26	.590	10