

Vinyl Insulated Locking Spade Terminals



MAXIMUM ELECTRIC CURRENT:


Awg	22	20	18	16	14	12	10
Amp	9	12	17	18	30	35	50

MAXIMUM ELECTRIC RATING: 167°F(75°C) 600 Volts

INSULATION MATERIAL: Vinyl

TERMINAL MATERIAL: Electro-Tin Plated Copper

FEATURES: Serrated Barrel, Expanded Insulation



Dimensions = Inches

Cat. No.	Color	Wire Size AWG	Stud Size	d2	W	F	L	E	D	d1	T	Bag Qty	Master Bag Qty
11702	Red	22-16	#6	.146	.252	.256	.874	.874	.134	.067	.030	100	1000
11704	Red	22-16	#8	.169	.319	.256	.874	.874	.134	.067	.030	100	1000
11706	Red	22-16	#10	.209	.319	.256	.874	.874	.134	.067	.030	100	1000
11708	Blue	16-14	#6	.146	.236	.256	.886	.453	.161	.091	.031	100	1000
11710	Blue	16-14	#8	.169	.319	.256	.886	.453	.161	.091	.031	100	1000
11712	Blue	16-14	#10	.209	.366	.256	.886	.453	.161	.091	.031	100	1000
11714	Yellow	12-10	#6	.146	.327	.276	1.035	.555	.248	.134	.039	100	1000
11716	Yellow	12-10	#8	.169	.327	.276	1.035	.555	.248	.134	.039	100	1000
11718	Yellow	12-10	#10	.209	.354	.276	1.035	.555	.248	.134	.039	100	1000
11720	Yellow	12-10	1/4	.252	.472	.472	1.283	.555	.248	.134	.039	100	1000

Nylon Insulated Locking Spade Terminals



MAXIMUM ELECTRIC CURRENT:


Awg	22	20	18	16	14	12	10
Amp	9	12	17	18	30	35	50

MAXIMUM ELECTRIC RATING: 221°F (105°C) 600 Volts

INSULATION MATERIAL: Nylon

TERMINAL MATERIAL: Electro-Tin Plated Copper - Brazed Seam

FEATURES: Serrated Barrel, Expanded Insulation



Dimensions = Inches

Cat. No.	Color	Wire Size AWG	Stud Size	d2	W	F	L	E	D	d1	T	Bag Qty	Master Bag Qty
11722	Red	22-16	#6	.146	.252	.256	.866	.433	.134	.067	.030	100	1000
11724	Red	22-16	#8	.169	.319	.256	.866	.433	.134	.067	.030	100	1000
11726	Red	22-16	#10	.209	.319	.256	.866	.433	.134	.067	.030	100	1000
11728	Blue	16-14	#6	.146	.236	.256	.866	.433	.161	.091	.031	100	1000
11730	Blue	16-14	#8	.169	.319	.256	.866	.433	.161	.091	.031	100	1000
11732	Blue	16-14	#10	.209	.366	.256	.866	.433	.161	.091	.031	100	1000
11734	Yellow	12-10	#6	.146	.327	.276	.992	.512	.252	.134	.039	100	1000
11736	Yellow	12-10	#8	.169	.327	.276	.992	.512	.252	.134	.039	100	1000
11738	Yellow	12-10	#10	.209	.354	.276	.992	.512	.252	.134	.039	100	1000
11740	Yellow	12-10	1/4	.252	.472	.472	1.240	.512	.252	.134	.039	100	1000