



MAXIMUM ELECTRIC CURRENT:

Awg	22	20	18	16	14	12	10
Amp	9	12	17	18	30	35	50

MAXIMUM ELECTRIC RATING: 167°F(75°C) 600 Volts

INSULATION MATERIAL: Vinyl

TERMINAL MATERIAL: Electro-Tin Plated Copper

FEATURES: Serrated Barrel, Expanded Insulation

Dimensions = Inches

Cat. No.	Color	Wire Size AWG	Stud Size	d2	W	F	L	E	D	d1	T	Bag Qty	Master Bag Qty
10010	Red	22-16	#4	.126	.217	.197	.736	.441	.157	.067	.031	100	1000
10012	Red	22-16	#6	.146	.260	.248	.811	.441	.157	.067	.031	100	1000
10014	Red	22-16	#8	.169	.315	.276	.866	.441	.157	.067	.031	100	1000
10016	Red	22-16	#10	.209	.315	.276	.866	.441	.157	.067	.031	100	1000
10018	Red	22-16	1/4	.252	.457	.433	1.102	.441	.157	.067	.031	100	1000
10020	Red	22-16	5/16	.331	.457	.433	1.102	.441	.157	.067	.031	100	1000
10022	Red	22-16	3/8	.413	.535	.547	1.248	.441	.157	.067	.031	100	1000
10023	Red	22-16	1/2	.512	.772	.630	1.441	.441	.157	.067	.031	100	1000
10024	Red	22-16	9/16	.591	1.063	.827	1.791	.441	.157	.067	.031	100	1000
10026	Red	22-16	5/8	.669	1.063	.827	1.791	.441	.157	.067	.031	100	1000
10028	Red	22-16	3/4	.827	1.063	.827	1.791	.441	.157	.067	.031	100	1000
10030	Blue	16-14	#4	.126	.260	.189	.760	.453	.177	.091	.031	100	1000
10032	Blue	16-14	#6	.146	.260	.248	.823	.453	.177	.091	.031	100	1000
10034	Blue	16-14	#8	.169	.335	.307	.917	.453	.177	.091	.031	100	1000
10036	Blue	16-14	#10	.209	.335	.307	.917	.453	.177	.091	.031	100	1000
10038	Blue	16-14	1/4	.252	.472	.433	1.114	.453	.177	.091	.031	100	1000
10040	Blue	16-14	5/16	.331	.472	.433	1.114	.453	.177	.091	.031	100	1000
10042	Blue	16-14	3/8	.413	.535	.547	1.260	.453	.177	.091	.031	100	1000
10044	Blue	16-14	1/2	.512	.756	.630	1.453	.453	.177	.091	.031	100	1000
10046	Blue	16-14	9/16	.591	1.063	.827	1.803	.453	.177	.091	.031	100	1000
10048	Blue	16-14	5/8	.669	1.063	.827	1.803	.453	.177	.091	.031	100	1000
10050	Blue	16-14	3/4	.827	1.063	.827	1.803	.453	.177	.091	.031	100	1000
10060	Yellow	12-10	#6	.146	.283	.240	.937	.555	.248	.134	.039	100	1000
10062	Yellow	12-10	#8	.169	.283	.240	.937	.555	.248	.134	.039	100	1000
10064	Yellow	12-10	#10	.209	.374	.327	1.024	.555	.248	.134	.039	100	1000
10066	Yellow	12-10	1/4	.252	.472	.413	1.205	.555	.248	.134	.039	100	1000
10068	Yellow	12-10	5/16	.331	.591	.524	1.382	.555	.248	.134	.039	100	1000
10070	Yellow	12-10	3/8	.413	.591	.524	1.382	.555	.248	.134	.039	100	1000
10072	Yellow	12-10	1/2	.512	.756	.630	1.563	.555	.248	.134	.039	100	1000
10074	Yellow	12-10	9/16	.591	1.260	.992	2.177	.555	.248	.134	.039	100	1000
10076	Yellow	12-10	5/8	.669	1.260	.992	2.177	.555	.248	.134	.039	100	1000
10078	Yellow	12-10	3/4	.827	1.260	.992	2.177	.555	.248	.134	.039	100	1000