

All Purpose 6200 Series Regular Bodied Clear Cements



- ▶ Regular Bodied Clear Cement for use on all schedules and classes of PVC, CPVC, ABS pipe and fittings up to 2" diameter with interference fit
- ▶ Low-Voc Solvent Cement meets California South Coast Air Quality Management District (SCAQMD) 1168/316A or BAAQMD Method 40 and various environmental requirements
- ▶ Recommended for Potable Water, Pressure Pipe and DWV
- ▶ Recommended application temperature 40°F to 110°F (4°C to 43°C)
- ▶ Meets performance requirements of ASTM D2564, D2235 and F493

Formulated For:
PVC, CPVC
& ABS
Pipe & Conduit

Cat. No.	Size	Case Qty.	Wt/Case
G6266S	1/4 Pt.	24	9
G6256S	1/2 Pt.	24	15
G6246S	1 Pt.	24	29
G6236S	1 Qt.	12	27

Black Cement 4400 Series Medium Body - ABS



- ▶ Medium-Bodied Black Cement for use on all schedules and classes of ABS pipe and fittings up to 6" diameter with interference fit
- ▶ Low-Voc Solvent Cement meets California South Coast Air Quality Management District (SCAQMD) 1168/316A or BAAQMD Method 40 and various environmental requirements
- ▶ For all Non-Pressure Applications
- ▶ Recommended application temperature 40°F to 110°F (4°C to 43°C)
- ▶ Meets ASTM D2235

Formulated For:
ABS
Pipe & Conduit

Cat. No.	Size	Case Qty.	Wt/Case
G4466S	1/4 Pt.	24	9
G4456S	1/2 Pt.	24	15
G4446S	1 Pt.	24	27
G4436S	1 Qt.	12	26
G4424	1 Gal.	6	50

Orange Cement 3200 Series Medium Body



- ▶ Medium-bodied Orange Cement for use on CPVC pipe and fittings up to 6" dia.
- ▶ Low-Voc Solvent Cement meets California South Coast Air Quality Management District (SCAQMD) 1168/316A or BAAQMD Method 40 and various environmental requirements
- ▶ Recommended application temperature 40°F to 110°F (4°C to 43°C)
- ▶ Recommended for hot and cold potable water pressure pipe
- ▶ Meets ASTM F493

Formulated For:
CPVC
Pipe & Conduit

Cat. No.	Size	Case Qty.	Wt/Case
G3266S	1/4 Pt.	24	9
G3256S	1/2 Pt.	24	16
G3246S	1 Pt.	24	30
G3236S	1 Qt.	12	29