


Rigid Nipples - Zinc Die Cast




- ▶ Use with Rigid Coupling to Terminate Threaded Conduit to a Knockout, Box or Enclosure, where space is limited within the box
- ▶ Used with a Locknut to provide a Short Raceway between Boxes and Enclosures

Dimensions = Inches

Cat. No.	Trade Size	Dimensions		Inner Box	Outer Box
		A	B		
14480	1/2"	.64	0.98	100	1000
14481	3/4"	.72	1.18	100	1000
14482	1"	.81	1.50	50	500
14483	1-1/4"	.94	1.77	25	250
14484	1-1/2"	1.07	2.17	25	150
14485	2"	1.08	2.60	15	90
14486	2-1/2"	1.09	3.09	-	20
14487	3"	1.25	3.71	-	20
14488	3-1/2"	1.27	4.24	-	10
14489	4"	1.27	4.70	-	10

Rigid Nipples with Insulated Throat - Zinc




- ▶ Use with Rigid Coupling to Terminate Threaded Conduit to a Knockout, Box or Enclosure where space is limited within the box
- ▶ Used with a Locknut to provide a Short Raceway between Boxes and Enclosures
- ▶ Insulated Throat

Dimensions = Inches

Cat. No.	Trade Size	Dimensions		Inner Box	Outer Box
		A	B		
14490	1/2"	.68	0.98	100	1000
14491	3/4"	.82	1.18	100	1000
14492	1"	.85	1.50	50	500
14493	1-1/4"	1.00	1.77	25	250
14494	1-1/2"	1.13	2.17	25	150
14495	2"	1.14	2.60	15	90
14496	2-1/2"	1.16	3.09	-	20
14497	3"	1.33	3.71	-	20
14498	3-1/2"	1.35	4.24	-	10
14499	4"	1.35	4.70	-	10

Thermoplastic Conduit Bushings



- ▶ Use with Locknut to Protect Conductors in Rigid or IMC Conduit from Abrasion/Damage during Pull
- ▶ Rounded surface of bushing prevents damage to wire insulation
- ▶ Thermoplastic material-heat, impact & torque resistant

Dimensions = Inches

Cat. No.	Trade Size	Dimensions		Inner Box	Outer Box
		A	B		
21732	1/2"	1.06	0.43	100	1000
21733	3/4"	1.31	0.43	100	1000
21734	1"	1.59	0.48	50	500
21735	1-1/4"	1.96	0.56	25	250
21736	1-1/2"	2.18	0.56	25	250
21737	2"	2.68	0.59	20	200
21738	2-1/2"	3.25	0.72	-	50
21739	3"	3.87	0.75	-	25
21740	3-1/2"	4.37	0.77	-	25
21741	4"	5.00	0.77	-	10
21742	5"	6.25	1.00	-	10
21743	6"	7.50	1.00	-	10