


Conduit Bushings - Zinc Die Cast




- ▶ Used with a locknut to terminate threaded Rigid and IMC conduit to a box or enclosure
- ▶ Bushings rounded surface prevents damage to wire insulation during pulling

Dimensions = Inches

Cat. No.	Trade Size	Dimensions			Inner Box	Outer Box
		A	B	C		
14530	1/2"	1.04	.59	.41	140	1400
14531	3/4"	1.28	.78	.43	100	1000
14532	1"	1.54	1.00	.49	50	500
14533	1-1/4"	1.89	1.31	.51	30	300
14534	1-1/2"	2.17	1.53	.51	20	200
14535	2"	2.64	1.99	.51	15	150
14536	2-1/2"	3.19	2.39	.73	-	75
14537	3"	3.82	2.99	.73	-	65
14538	3-1/2"	4.31	3.47	.73	-	50
14539	4"	4.84	3.95	.73	-	40

Conduit Bushings with Insulated Throat - Zinc Die Cast




- ▶ Used with a locknut to terminate threaded Rigid and IMC conduit to a box or enclosure
- ▶ Bushings rounded surface prevents damage to wire insulation during pulling
- ▶ Insulated Throat

Dimensions = Inches

Cat. No.	Trade Size	Dimensions			Inner Box	Outer Box
		A	B	C		
14540	1/2"	1.06	.53	.45	140	1400
14541	3/4"	1.28	.78	.47	100	1000
14542	1"	1.53	1.00	.53	50	500
14543	1-1/4"	1.89	1.31	.59	30	300
14544	1-1/2"	2.17	1.53	.59	20	200
14545	2"	2.64	1.99	.59	15	150
14546	2-1/2"	3.19	2.63	.79	-	75
14547	3"	3.82	2.95	.81	-	65
14548	3-1/2"	4.31	3.41	.81	-	50
14549	4"	4.84	3.91	.81	-	40

Grounding Bushing Insulated Throat with Aluminum Lug - Zinc



- ▶ Used with a locknut to terminate threaded Rigid & IMC conduit to a box or enclosure and to provide a smooth pulling surface
- ▶ Thermoplastic liner prevents damage to wire insulation
- ▶ Lug provides for bonding jumper to a neutral bus bar
- ▶ Resists corrosion, chemicals, and temperature extremes
- ▶ Set-screw provided with each fitting locks bushing in any desired position

Dimensions = Inches

Cat. No.	Trade Size	Grounding Lug Range	Dimensions			Inner Box	Outer Box
			A	B	C		
14570	1/2"	#14 - #4	1.06	.59	.53	50	500
14571	3/4"	#14 - #4	1.28	.78	.53	40	400
14572	1"	#14 - #4	1.53	1.00	.63	25	250
14574	1-1/4"	#14 - #4	1.87	1.31	.65	25	250
14576	1-1/2"	#14 - #2	2.17	1.52	.69	25	250
14578	2"	#14 - #2	2.66	1.99	.69	10	100
14579	2-1/2"	#14 - #1/0	3.23	2.34	.91	5	50
14581	3"	#14 - #1/0	3.84	2.95	.91	5	50
14583	3-1/2"	#14 - #2/0	4.33	3.39	.91	4	40
14585	4"	#14 - #2/0	4.84	3.86	.91	4	40