

Flex Duplex Box Connectors - Zinc Die Cast



Fig 1




Fig 1

- ▶ Use to connect two pieces of Flexible Metallic Conduit, AC, MC, or NM sheathed cable to a steel box or other metal enclosure when using only one knockout opening:
 - 14/2 Thru 12/3 NM
 - 14/2 Thru 10/4 AC
 - 14/2 Thru 10/3 MC
 - 3/8" FMC
- ▶ 3/8" size fits 1/2" knockout
- ▶ One Screw or Two Screw design



Fig 2





Fig 2

Dimensions = Inches

Cat. No.	Trade Size	Figure	# of Screws	Dimensions			Inner Box	Outer Box
				A	B	C		
15065	3/8"	1	1	1.43	.61	1.61	25	250
15066	3/8"	2	2	1.57	.61	2.32	25	250

90° Flex Conduit Duplex Box Connector - Zinc Die Cast




- ▶ Use to connect two pieces of Flexible Metallic Conduit, AC, MC or NM sheathed cable to a steel outlet box or other metal enclosure when using only one knockout opening in a dry location:
 - 14/2 Thru 10/3 NM
 - 14/2 Thru 10/4 AC
 - 14/2 Thru 10/3 MC
 - 3/8" FMC
- ▶ 3/8" size fits 1/2" knockout
- ▶ Two Combo Head Mounting Screws

Dimensions = Inches

Cat. No.	Trade Size	Dimensions			Inner Box	Outer Box
		A	B	C		
15067	3/8"	2.02	1.64	1.24	25	250

Anti-Short Bushings



- ▶ Insulates conductor from cut armor ends on flexible BX or Greenfield conduit
- ▶ Inserted into I.D. at termination point
- ▶ Overlapping horizontal flange protects against sharp metal edges
- ▶ Tapered design assures fast insertion
- ▶ Extra length assures positive grip
- ▶ Polypropylene material resists weather extremes, oil, moisture and chemicals
- ▶ Rated up to 194°F

Dimensions = Inches

Cat. No.	Size	Cable Sizes	Dimensions				Bag Qty
			A	B	C	D	
21752	0	14/2, 14/3, 12/2	0.56"	0.671"	0.38"	0.312"	35
21753	1	14/4, 12/3, 6/1, 4/1	0.65"	0.671"	0.45"	0.312"	35
21754	2	12/4, 10/2, 10/3, 2/1	0.61"	0.859"	0.58"	0.125"	35
21755	3	10/4, 8/2, 8/3, 1/1	0.67"	1.046"	0.79"	0.109"	20
21756	4	8/4, 6/4, 6/3, 6/2, 4/3, 4/2	0.83"	1.266"	1.00"	0.156"	16