

Nylon Cable Glands - Multi-Conductor - NPT Thread



- ▶ Same features as Nylon Cable Gland on previous page
- ▶ Multi-Hole Design organizes Multiple Cables within a Gland
- ▶ Easy to Assemble
- ▶ Wide Clamping Range
- ▶ -22°F to 140°F Temperature Rating
- ▶ UV Resistant Black
- ▶ Made of UL Approved NYLON 66
- ▶ Flammability Rating: 94V-2
- ▶ IP68 Rated Submersible & Dustproof

Dimensions = Inches

Cat. No.	NPT Thread	Cable Range	D1	L1	Bag Qty	Master Bag
2 Hole Gland						
22230	1/4	.078 - .122	.52	.31	10	100
22231	3/8	.064 - .102	.66	.57	10	100
22232	3/8	.078 - .122	.66	.57	10	100
22233	3/8	.119 - .161	.66	.57	10	100
22234	1/2	.064 - .102	.83	.51	10	100
22235	1/2	.098 - .138	.83	.51	10	100
22236	1/2	.130 - .170	.83	.51	10	100
22237	1/2	.157 - .240	.83	.51	10	100
22238	3/4	.098 - .138	1.04	.57	10	100
22239	3/4	.138 - .200	1.04	.57	10	100
22240	3/4	.200 - .256	1.04	.57	10	100
22241	3/4	.252 - .343	1.04	.57	10	100
22242	1	.142 - .205	1.31	.59	10	100
22243	1	.200 - .256	1.31	.59	10	100
22244	1	.252 - .343	1.31	.59	10	100
22245	1	.303 - .394	1.31	.59	10	100
22246	1-1/4	.276 - .354	1.65	.72	10	100
22247	1-1/4	.433 - .512	1.65	.72	10	100

3 Hole Gland						
22248	1/4	.063 - .102	.52	.31	10	100
22249	3/8	.063 - .102	.66	.57	10	100
22250	3/8	.118 - .165	.66	.57	10	100
22251	1/2	.078 - .118	.83	.51	10	100
22252	1/2	.118 - .165	.83	.51	10	100
22253	1/2	.138 - .205	.83	.51	10	100
22254	3/4	.102 - .142	1.04	.57	10	100
22255	3/4	.142 - .205	1.04	.57	10	100
22256	3/4	.189 - .244	1.04	.57	10	100
22257	3/4	.244 - .315	1.04	.57	10	100
22258	1	.142 - .205	1.31	.59	10	100
22259	1	.189 - .244	1.31	.59	10	100
22260	1	.244 - .315	1.31	.59	10	100
22261	1	.303 - .394	1.31	.59	10	100
22262	1-1/4	.256 - .327	1.65	.72	10	100
22263	1-1/4	.303 - .394	1.65	.72	10	100


4 Hole Gland						
22264	1/4	.051 - .091	.52	.31	10	100
22265	3/8	.051 - .091	.66	.57	10	100
22266	3/8	.094 - .134	.66	.57	10	100
22267	1/2	.055 - .094	.83	.51	10	100
22268	1/2	.094 - .134	.83	.51	10	100
22269	1/2	.134 - .189	.83	.51	10	100
22270	3/4	.063 - .098	1.04	.57	10	100
22271	3/4	.098 - .142	1.04	.57	10	100
22272	3/4	.150 - .205	1.04	.57	10	100
22273	3/4	.220 - .287	1.04	.57	10	100
22274	1	.079 - .122	1.31	.59	10	100
22275	1	.118 - .161	1.31	.59	10	100
22276	1	.150 - .205	1.31	.59	10	100
22277	1	.220 - .287	1.31	.59	10	100
22278	1	.276 - .354	1.31	.59	10	100
22279	1-1/4	.394 - .472	1.65	.72	10	100

Dimensions = Inches

Cat. No.	NPT Thread	Cable Range	D1	L1	Bag Qty	Master Bag
5 Hole Gland						
22280	3/8	.079 - .110	.66	.57	10	100
22281	1/2	.051 - .079	.83	.51	10	100
22282	1/2	.079 - .110	.83	.51	10	100
22283	1/2	.118 - .161	.83	.51	10	100
22284	3/4	.047 - .079	1.04	.57	10	100
22285	3/4	.079 - .122	1.04	.57	10	100
22286	3/4	.118 - .161	1.04	.57	10	100
22287	3/4	.142 - .181	1.04	.57	10	100
22288	3/4	.181 - .236	1.04	.57	10	100
22289	1	.102 - .142	1.31	.59	10	100
22290	1	.142 - .181	1.31	.59	10	100
22291	1	.181 - .237	1.31	.59	10	100
22292	1	.237 - .315	1.31	.59	10	100
22293	1-1/4	.256 - .327	1.65	.72	10	100

6 Hole Gland						
22294	3/8	.055 - .083	.66	.57	10	100
22295	1/2	.051 - .079	.83	.51	10	100
22296	1/2	.079 - .118	.83	.51	10	100
22297	3/4	.055 - .083	1.04	.57	10	100
22298	3/4	.079 - .118	1.04	.57	10	100
22299	3/4	.102 - .142	1.04	.57	10	100
22300	3/4	.142 - .205	1.04	.57	10	100
22301	1	.102 - .142	1.31	.59	10	100
22302	1	.142 - .205	1.31	.59	10	100
22303	1	.220 - .276	1.31	.59	10	100

7 Hole Gland						
22304	1/2	.051 - .079	.83	.51	10	100
22305	1/2	.079 - .118	.83	.51	10	100
22306	3/4	.051 - .079	1.04	.57	10	100
22307	3/4	.079 - .118	1.04	.57	10	100
22308	3/4	.102 - .142	1.04	.57	10	100
22309	1	.102 - .142	1.31	.59	10	100
22310	1	.181 - .236	1.31	.59	10	100



Cable Glands Fittings

M36