



MORRIS CAT#: 23007-23010

12 AWG Push-In Wire Connectors



Features:

- Easy Push-In Wire Connectors are simple to install - instead of Twisting or Taping, simply Push Wires Into Contact Port to save you time and money
- Accepts Either Stranded or Solid Wire
- Low Wire Insertion Force allows fast, easy connections
- No-Twist Connection reduces repetitive motion fatigue
- See-thru for visual connection inspection
- Test Port for Continuity Testing
- Electrolytic Tin-Plated Internal Copper Bus for high conductivity
- Housing Material: Polycarbonate, UL 94V-2 flame retardant
- Current: 24A or 32A
- Voltage: 600V
- Working Temperature: 221°F (105°C)
- UL Listed for Copper Conductors only

DIMENSIONS = INCHES

<i>CAT. NO.</i>	<i>POLES</i>	<i>COLOR</i>	<i>VOLTS</i>	<i>AMPS</i>	<i>WIRE RANGE STRANDED</i>	<i>WIRE RANGE SOLID</i>	<i>L</i>	<i>W</i>	<i>H</i>	<i>QTY</i>	<i>CASE QTY</i>
BOX OF 100											
23007*	2	RED	600	32	16-12	18-12	.78	.52	.32	100	6,000
23008*	4	RED	600	32	16-12	18-12	.78	.52	.54	100	6,000
BULK BAG											
23009*	2	RED	600	32	16-12	18-12	.78	.52	.32	300	6,000
23010*	4	RED	600	32	16-12	18-12	.78	.52	.54	200	4,000

* NOTE: UL LISTED FOR 18-12 AWG ONLY