



MORRIS CAT#: 23222A-23228A

22-14 AWG Push-In Wire Connectors



Features:

- Easy Push-In Wire Connectors are simple to install - instead of Twisting or Taping, simply Push Wires Into Contact Port to save you time and money
- Accepts Either Stranded or Solid Wire
- Low Wire Insertion Force allows fast, easy connections
- No-Twist Connection reduces repetitive motion fatigue
- See-thru for visual connection inspection
- Test Port for Continuity Testing
- Electrolytic Tin-Plated Internal Copper Bus for high conductivity
- Housing Material: Polycarbonate, UL 94V-2 flame retardant
- Current: 24A or 32A
- Voltage: 600V
- Working Temperature: 221°F (105°C)
- UL Listed for Copper Conductors only

DIMENSIONS = INCHES

CAT. NO.	POLES	COLOR	VOLTS	AMPS	WIRE RANGE STRANDED	WIRE RANGE SOLID	L	W	H	QTY	CASE QTY
BULK BAG											
23222A	2	RED	600	24	18-14	20-14	.76	.41	.43	250	5,000
23223A	3	ORANGE	600	24	18-14	20-14	.76	.53	.43	200	4,000
23224A	4	YELLOW	600	24	18-14	20-14	.76	.69	.43	150	3,000
23225A	5	GRAY	600	24	18-14	20-14	.76	.83	.43	100	2,000
23228A	8	BLACK	600	24	18-14	20-14	.76	1.25	.43	50	1,000