



Cat# 60000-60090
Economy Grade
Vinyl Electrical Tape

Recommended Uses:

Used for general splicing purposes. Can be used as primary insulation for splices up to 600 volts and provides a protective outer jacket for splices at higher voltages. Can be used for wrapping wire harnesses and insulating degaussing coils. Colors can be used for color coding electrical circuits.

Description:

A 7 mil (0.18) commercial grade, weather resistant, pressure sensitive vinyl tape for all kinds of mechanical and electrical applications. MORRIS flame retardant and can be used as primary insulation for splices up to 600 volts. UL 510, CSA 22.2 Lead-free.

Specifications:

Property	Value	Unit	Test Method
physical			
Thickness	0.007	inch	ASTM-D-1000
	0.178	mm	
Tensile Strength	16	1b/in	ASTM-D-1000
	28.16	n/cm	
Elongation	150	%	ASTM-D-1000
Adhesion to Steel	20	oz/in	ASTM-D-1000
	2.2	n/cm	
Adhesion to Backing	17	oz/in	ASTM-D-1000
	1.8	n/cm	
Flammability	4 max	second	ASTM-D-1000
Temperature Rating	80	°C	UL 510
		°C	CSA 22.2
	0	°C	UL 510
Minimum	0	°C	CSA 22.2
		-	ASTM-D-1000
Dielectric Strength	7,000	-	ASTM-D-1000

Data in table represent average test results and are not to be used for specification purposes. The product user should make his/her own tests to determine the product's suitability for the intended use.

Features

- 7 mil thickness
- Flame retardant
- Lead-free
- Resistant to sun, water, oil, acids, alkalis, corrosive chemicals

Product Approvals

- UL 510
- CSA 22.2

Standard Sizes

- 3/4 in x 60 ft
 - 19 mm x 18 m
- Consult factory for other sizes

Colors

- Black ● Orange
- Red ● Green
- White ● Violet
- Blue ● Brown
- Yellow ● Grey