

# LED EXIT SIGN RED LETTERS & LEDs, BLACK HOUSING

## 7-0000-0

- Superior Quality Exit Unit Combined with LED Energy Saving Technology
- Completely Self-Contained
- Fully Automatic Operation
- Compact, Low Profile Design in Neutral Finish
- Push to Test Switch in Battery Backup Units
- Automatic, Low Voltage Disconnect (LVD)
- 120 or 277 VAC Operation
- Injection-Molded, UL 94 V-0 Flame Retardant, High Impact Housing
- Charge Rate/Power On LED Indicator Light
- Energy Consumption Less than 4 W Red Legend 2 W Green legend
- Listed for Damp Location
- Universal Mounting Canopy & 2 Face Plates for Side or Top Installation
- Standard AC and Emergency Units Available
- 700MAH 4.8V Ni-CAD Battery On Battery Backup Units
- 90 Minute Battery Run Time
- Red LEDs

Part#	Housing Color	LED Color	Battery Backup	Voltage
7301H	Black	Red	Y^•	120/277V

### TECHNICAL SPECIFICATIONS:

#### Packaging:

Box Qty: 1  
Master Carton Qty: 6  
Warranty: 3 Years  
UPC Number: 60198673013

#### Certifications:

cULus  
RoHS

Input Rating Amps: 18.1 mA @120V, 7.76 mA @ 277V  
Input Rating Watts: 1.64W @ 120V 1.60W @ 277V  
Frequency: 60 Hz  
Voltage Rating: 120/277  
Flammability Rating: UL 94 V-0  
Battery Operation: 4.8 Volt 4.5 AH Lead Acid - 90 Minutes Min