





# 73452 - LED EXIT SIGN

## RED LETTERS, WHITE HOUSING

WET LOCATION



### FEATURES:

- Flame Retardant, UV-stabilized corrosion & impact resistant
- Polycarbonate Housing Clear Polycarbonate Cover Enclosure resistant to corrosive atmospheres, non-hazardous dust environment, hose-down water spray or splashing water
- Universal canopy provides top, end or back mount convenience
- 2 Face Plates for Side or Top Installation
- Universal K/O Pattern on back plate for wall mount Engineering
- Grade Rubber Gasket
- Top and Side K/O's provided for conduit feed applications
- EZ Snap-out chevron directional indicators
- Meets UL924 for Wet Locations
- 3 Year Warranty

Part#	Housing Color	LED Color	Remote Capable	Voltage
73452	White	Red	No	120/277V

### TECHNICAL SPECIFICATIONS:

#### Specifications:

Amperage Rating: 20.7mA@120V 8.9mA@277V

Wattage Rating: 1.89W @ 120V 1.86W @ 277V

Voltage Rating: 120/277

Flammability Rating: UL94V-2

Operating Temperature: 50°F - 104°F

#### General:

Material: Polycarbonate housing, Clear polycarbonate cover

Lamp Type: LED

Battery: 2.4V 500mAH Ni-CD

Emergency power: 90 minutes

UPC: 60198673452

#### Packaging:

Box Qty: 1

Master Box Qty: 4

#### Certifications:

UL: 924 for Wet Locations