




73452 - LED EXIT SIGN

RED LETTERS, WHITE HOUSING

WET LOCATION



- Flame Retardant, UV-stabilized corrosion & impact resistant
- Polycarbonate Housing Clear Polycarbonate Cover Enclosure resistant to corrosive atmospheres, non-hazardous dust environment, hose-down water spray or splashing water
- Universal canopy provides top, end or back mount convenience

- 2 Face Plates for Side or Top Installation
- Universal K/O Pattern on back plate for wall mount Engineering
- Grade Rubber Gasket
- Top and Side K/O's provided for conduit feed applications
- EZ Snap-out chevron directional indicators
- Meets UL924 for Wet Locations
- 3 Year Warranty

DUf'h .	< c i g]' b [7 c ` ' c f	@9 8 ' c ` ' c f	F Y a c h Y ` 7 U d U V ` Y c ` h U [Y
+ ' () &	White	Red	% & \$ # & + + J

TECHNICAL SPECIFICATIONS:

Specifications:

Amperage Rating: 20.7mA@120V 8.9mA@277V
 Wattage Rating: 1.89W @ 120V 1.86W @ 277V
 Voltage Rating: 120/277
 Flammability Rating: UL94V-2

Packaging:

Box Qty: 1
 Master Box Qty: 4

Certifications:

UL: 924 for Wet Locations

General:

Material: Polycarbonate housing, Clear polycarbonate cover
 Lamp Type: LED
 Battery: 2.4V 500mAH Ni-CD
 Emergency power: 90 minutes
 UPC: 60198673452