



73522 - ROUND HEAD EMERGENCY LIGHT

WHITE, STANDARD WITH SELF DIAGNOSTIC



FEATURES:

- Self DiagnosticTest Feature continually diagnoses units performance and tests system to ensure reliable operation and to meet electrical & Life Safety Codes
- Completely Self-Contained
- Fully Automatic Operation
- Compact, Low Profile Designs in Neutral Finish
- Push to Test Switch
- 3.6 Volt Maintenance Free Ni-Cad Battery
- Environmental Coated, Solid State Charger
- 2 x 12 LED 76 Lumen Fully Adjustable Glare Free Lamps
- Automatic, Low Voltage Disconnect (LVD)
- Universal Transformer for 120 or 277 VAC
- Universal J-Box Mounting Plate
- Injection Molded, V-O Flame Retardant, High Impact, Thermoplastic Housing
- Charge Rate/Power on LED Indicator Light
- 90 Minute Emergency Operation
- Damp Location Rated
- Self Diagnostic Features:
On-Line real time monitoring of battery charging, disconnection or failure and local or remote lamp failure Self Testing and 15 Minute discharge every 30 days Self Testing and 90 Minute discharge annually

Part#	Type	Volts	Lumens per head	Housing Color	Battery
73522	Self Diagnostic	120/277	33	White	Ni-Cad

Dimension Information

L Inches (mm)	9
H Inches (mm)	4.00
Depth Inches (mm)	2.75

Specifications

Input Rating Amps:	1.03
Input Rating Watts:	.85 @ 120V .80 @ 277V
Lamp Type: Voltage	LED 76 Lumens Per Head
Rating: Flammability	120/277
Rating: Battery	UL94V-0
Operation:	3.6 Volt Nickel Cadmium - 90 Minutes Min

Packaging

Box Qty	1
Master Carton Qty	12
Certifications	
UL	UL 924
cUL	No
RoHS	Yes