



**MORRIS CAT#: 89752 - 89761**  
**Twist Lock Plugs and Receptacles**  
**3 Pole 4 Wire**



**FIG 3**



**FIG 4**

**Features:**

- Commonly used with most generators
- Rugged Nylon/Polycarbonate Construction resists impact, abrasion, sunlight & chemicals
- Grooved Housing for enhanced grip
- All contacts are solid one-piece brass for superior conductivity and reduced heat rise
- Includes grounding screw
- cULus Listed
- Heavy duty power contacts set in deep pockets to resist damage
- Heavy duty brass combo head terminal screws
- Clear terminal chamber allows for visual inspection of terminals
- Cord strain relief and rubber grommet to seal from environment

<b>CAT. NO.</b>	<b>MALE/FEMALE</b>	<b>FIGURE</b>	<b>AMPS</b>	<b>VOLTS</b>	<b>NEMA#</b>	<b>BOX QTY</b>	<b>MASTER BOX QTY</b>
<b>3 POLE 4 WIRE</b>							
89752	MALE	3	20	125/250	L14-20P	10	100
89754	FEMALE	4	20	125/250	L14-20C	10	100
89755	MALE	3	20	250	L15-20P	10	100
89757	FEMALE	4	20	250	L15-20C	10	100
<b>NEW</b> 20464	MALE	3	20	480	L16-20P	10	100
<b>NEW</b> 20465	FEMALE	4	20	480	L16-20C	10	100
89756	MALE	3	30	125/250	L14-30P	10	100
89758	FEMALE	4	30	125/250	L14-30C	10	100
89760	MALE	3	30	250	L15-30P	10	100
89761	FEMALE	4	30	250	L15-30C	10	100
<b>NEW</b> 20469	MALE	3	30	480	L16-30P	10	100
<b>NEW</b> 20470	FEMALE	4	30	480	L16-30C	10	100