



Morris CAT#: 91500-91524

Irreversible Grounding



Features:

- Made of Pure Electrolytic Copper - matches or exceeds conductor current carrying capacity
- Acceptable for direct burial in earth and concrete
- Provides a tap or pigtail-type connection from ground rods to grounding counterpoise or grid
- Conductor range #2 through 500 kcmil
- Suitable for use on Copperweld™ or copper clad cable
- Ground rod sizes 1/2", 5/8", 3/4" and 1"
- UL 467 Listed and meets UL 96 Std.
- CSA Certified, and conforms to IEEE 837 Std.

DIMENSIONS = INCHES

| CAT. NO. | WIRE RANGE | ROD/REBAR DIAMETER | DIMENSIONS INCHES | | BOX QTY |
|----------|------------|--------------------|-------------------|--------|---------|
| | | | DEPTH/WIDTH | HEIGHT | |
| 91500 | #2-2/0 | 1/2" | .88 | 1.94" | 50 |
| 91502 | #2-2/0 | 5/8" | .88 | 1.97" | 50 |
| 91504 | #2-2/0 | 3/4" | .88 | 2.19" | 40 |
| 91506 | #2-2/0 | 1" | .88 | 2.55" | 40 |
| 91510 | 2/0-250 | 1/2" | .88 | 1.40" | 50 |
| 91512 | 2/0-250 | 5/8" | .88 | 2.14" | 40 |
| 91514 | 2/0-250 | 3/4" | .88 | 2.19" | 40 |
| 91516 | 2/0-250 | 1" | .88 | 2.45" | 40 |
| 91520 | 250-500 | 5/8" | .88 | 2.14" | 40 |
| 91522 | 250-500 | 3/4" | .88 | 2.44" | 35 |
| 91524 | 250-500 | 1" | .88 | 2.45" | 40 |