



Morris CAT#: 91530-91549

Irreversible Grounding



Fig 1



Fig 2

Features:

- Made of Pure Electrolytic Copper - matches or exceeds conductor current carrying capacity
- Acceptable for direct burial in earth and concrete
- Provides a tap or pigtail connection from ground rods to grounding counterpoise or grid
- Conductor range #6 through 500 kcmil
- Suitable for use on Copperweld™ or copper clad cable
- Ground rod sizes 1/2", 5/8", and 3/4"
- UL 467 Listed and meets UL 96 Std.
- CSA Certified, and conforms to IEEE 837 Std.

DIMENSIONS = INCHES

| CAT. NO. | FIG | CONDUCTOR/GROUND ROD TO CONDUCTOR WIRE RANGE | | REBAR TO CONDUCTOR | | DIMENSIONS INCHES | | BOX QTY |
|----------|-----|--|-----------------|--------------------|------------------|-------------------|--------|---------|
| | | MAIN | TAP | MAIN | TAP | DEPTH/WIDTH | HEIGHT | |
| 91530 | 1 | #2 STR | #6 SOL | - | - | .88 | 1.94 | 75 |
| 91532 | 2 | #2 STR | #6 SOL | - | - | .88 | 1.97 | 75 |
| 91534 | 2 | 250-1/0 1/2"-5/8" ROD | #6 STR-#8 SOL | #3(3/8")-#4(1/2") | #6 STR-#8 SOL | .88 | 2.19 | 50 |
| 91536 | 1 | 250-1/0 1/2"-5/8" ROD | #2 STR-#4 SOL | #3(3/8")-#4(1/2") | #2 STR | .88 | 2.55 | 15 |
| 91540 | 1 | 250-1/0 1/2"-5/8" ROD | 2/0 STR-1/0 STR | #3(3/8")-#4(1/2") | 2/0 STR-1/0 STR | .88 | 1.40 | 15 |
| 91542 | 1 | 250-1/0 1/2"-5/8" ROD | 250-3/0 STR | #3(3/8")-#4(1/2") | 250 MCM-3/0 STR | .88 | 2.14 | 15 |
| 91544 | 1 | 500-250 3/4"-5/8" ROD | #2 STR-#4 STR | #5(5/8")-#6(3/4") | - | .88 | 2.19 | 15 |
| 91546 | 1 | 500-250 3/4"-5/8" ROD | 2/0 STR-1/0 STR | #5(5/8")-#6(3/4") | 2/0 STR-1/0 STR | .88 | 2.45 | 15 |
| 91547 | 1 | 500-250 3/4"-5/8" ROD | 250-3/0 STR | #5(5/8")-#6(3/4") | 250 MCM-3/0 STR | .88 | 2.14 | 15 |
| 91549 | 1 | 500-250 3/4"-5/8" ROD | 500-350 MCM | #5(5/8")-#6(3/4") | 500- MCM-350 MCM | .88 | 2.44 | 15 |