



# Thin Wall Heat Shrink Tubing - 4' Length

- Flexible Polyolefin Heat Shrink Tubing
- 2:1 Shrink Ratio
- 600 Volt
- 257°F (125°C) Continuous Operation
- For Insulating, Wire Harness, Wire Bundling, Splicing & Terminations
- UL 224 Recognized



**MORRIS**  
**CONNECTORS**  
Heat Shrink

<b>CAT NO.</b>	<b>LENGTH</b>	<b>COLOR</b>	<b>DIAMETER BEFORE SHRINKING</b>	<b>DIAMETER AFTER SHRINKING</b>	<b>BAG QTY</b>
68072	4'	BLACK	0.078"	0.029"	1
68074	4'	BLACK	0.098"	0.039"	1
68076	4'	BLACK	0.137"	0.059"	1
68078	4'	BLACK	0.211"	0.098"	1
68080	4'	BLACK	0.250"	0.117"	1
68082	4'	BLACK	0.367"	0.176"	1
68084	4'	BLACK	0.484"	0.234"	1
68086	4'	BLACK	0.827"	0.390"	1
68088	4'	BLACK	1.26"	0.590"	1
68382	4'	CLEAR	0.078"	0.029"	1
68383	4'	CLEAR	0.098"	0.039"	1
68384	4'	CLEAR	0.137"	0.059"	1
68385	4'	CLEAR	0.211"	0.098"	1
68386	4'	CLEAR	0.250"	0.117"	1
68387	4'	CLEAR	0.367"	0.176"	1
68388	4'	CLEAR	0.484"	0.234"	1
68389	4'	CLEAR	0.827"	0.390"	1
68391	4'	RED	0.078"	0.029"	1
68392	4'	RED	0.098"	0.039"	1
68393	4'	RED	0.137"	0.059"	1
68394	4'	RED	0.211"	0.098"	1
68395	4'	RED	0.250"	0.117"	1
68396	4'	RED	0.367"	0.176"	1
68397	4'	RED	0.484"	0.234"	1
68398	4'	RED	0.827"	0.390"	1
68399	4'	RED	1.26"	0.590"	1
68401	4'	GREEN	0.098"	0.039"	1
68403	4'	GREEN	0.211"	0.098"	1
68404	4'	GREEN	0.250"	0.117"	1
68405	4'	GREEN	0.367"	0.176"	1
68406	4'	GREEN	0.484"	0.234"	1
68407	4'	GREEN	0.827"	0.390"	1
68409	4'	WHITE	0.078"	0.029"	1
68410	4'	WHITE	0.098"	0.039"	1
68411	4'	WHITE	0.137"	0.059"	1
68412	4'	WHITE	0.211"	0.098"	1
68413	4'	WHITE	0.250"	0.117"	1
68414	4'	WHITE	0.367"	0.176"	1
68415	4'	WHITE	0.484"	0.234"	1
68416	4'	WHITE	0.827"	0.390"	1
68417	4'	WHITE	1.26"	0.590"	1
68420	4'	BLUE	0.137"	0.059"	1
68421	4'	BLUE	0.211"	0.098"	1
68422	4'	BLUE	0.250"	0.117"	1
68423	4'	BLUE	0.367"	0.176"	1
68424	4'	BLUE	0.484"	0.234"	1
68425	4'	BLUE	0.827"	0.390"	1
68426	4'	BLUE	1.26"	0.590"	1