

Insulated Splices - Dual Side Entry



- Dual Side Entry
- 6061-T6 Aluminum
- Insulated with Rugged High-Dielectric Plastisol Dipped Coating
- Pre-filled with Oxide Inhibitor
- Easy Re-Entry for Changes, Inspection or Troubleshooting
- Plugs Marked with Connector Max Wire Size for Easy Identification
- CUSAL Dual Rated for use with Copper and/or Aluminum Wire
- One Wire Per Terminal
- Temperature Range of -49°F to 194°F (-45° to 90°C)
- 600 Volts
- Rated For Use with 90°C Cables
- UL Listed Through 750 MCM
- UL 486A/486B Listed
- **Indoor Use Only**

Insulated Connectors CONNECTORS

CAT. NO.	WIRE PORTS	WIRE RANGE	ALLEN HEX	DIMENSIONS		BOX QTY
				LENGTH	HEIGHT	
97613	3			1.50"		12
97614	4			1.92"		6
97615	5	4 - 14	SLOTTED/ HEX	2.33"	1.45"	6
97616	6			2.75"		4
97618	8			3.59"		3
97624	3			1.60"		6
97625	4			2.02"		6
97626	5	2 - 14	SLOTTED/ HEX	2.43"	1.50	6
97627	6			2.85"		4
97629	8			3.69"		3
97633	3			1.90"		8
97634	4			2.49"		6
97635	5			3.08"		4
97636	6	2/0 - 6	3/16"	3.67"	1.85"	4
97638	8			4.85"		3
97640	10			6.03"		3
97642	12			7.21"		4
97683	3			2.10"		6
97684	4			2.87"		6
97685	5			3.64"		4
97686	6	3/0 - 6	1/4"	4.41"	1.99"	3
97688	8			5.96"		3
97690	10			7.50"		3
97692	12			9.04"		3
97643	3			2.40"		6
97644	4			3.29"		4
97645	5			4.17"		4
97646	6	250 - 6	5/16"	5.06"	2.49"	4
97647	7			5.94"		3
97648	8			6.83"		3
97650	10			8.60"		3
97652	12			10.37"		3

CAT. NO.	WIRE PORTS	WIRE RANGE	ALLEN HEX	DIMENSIONS		BOX QTY
				LENGTH	HEIGHT	
97653	3			2.80"		6
97654	4			3.85"		4
97655	5			4.90"		4
97656	6	350 - 6	5/16"	5.95"	2.64"	3
97658	8			8.06"		3
97659	9			9.11"		3
97660	10			10.16"		3
97662	12			12.26"		3
97693	3			3.18"		4
97694	4			4.35"		4
97695	5			5.53"		4
97696	6	500 - 4	5/16"	6.70"	3.03"	2
97698	8			9.05"		2
97699	9			10.22"		2
97700	10			11.39"		2
97702	12			13.74"		2
97663	3			3.40"		4
97664	4			4.68"		4
97665	5			5.95"		4
97666	6	600 - 250	5/16"	7.23"	3.11"	2
97668	8			9.78"		2
97669	9			11.05"		2
97670	10			12.33"		2
97672	12			14.88"		2
97673	3			3.60"		4
97674	4			5.03"		4
97675	5			6.45"		4
97676	6	750 - 250	3/8"	7.88"	3.60"	4
97678	8			10.73"		2
97679	9			12.15"		2
97680	10			13.58"		2
97682	12			16.43"		2