

February 2017

<http://media.diversitech.com/doc/DOC32935.pdf>

Page 1 of 1

DiversiTech Electrical Disconnects

Disconnects - Metal Case

Fused model designed with fuses in pull-out handle for easy replacement. The line, load, and ground terminals are aligned for ease of wiring. This product has a reversible door which opens to either the left or right. The side open door opens more than 180 degrees for maximum access and has a full dead front. The fused models have indicator lights for blown fuses. This is rain tight and sleet resistant. The UL Listed number is IRF9, NEMA Type 3R and the US Patent is 6,630,637.



Catalog No.	Description	UOM	Order Multiple
TDDS-30	30A fusible disconnect switch	EA	10
TDDS-60	60A fusible disconnect switch	EA	10
TDDS-60U	60A non-fusible disconnect switch	EA	10

Low-Profile Disconnects - Metal Case

This low profile disconnect switch is a slightly smaller design than that of the standard DiversiTech disconnects. This has a side opening door with a full dead front. This is rain tight and sleet resistant. The UL Listed number is IRF9, NEMA Type 3R.



Catalog No.	Description	UOM	Order Multiple
TEDS-12-6NM	Disconnect and Whip combo kit - 60AMP	EA	3
TEDS-60U	60A non-fusible disconnect switch	EA	10

Disconnects - Non-Metallic Case

All the features of standard DiversiTech electrical disconnects, but in a non-metallic case that will not corrode.



Catalog No.	Description	UOM	Order Multiple
T750-P60NF	60A Non-Fusible Disconnect Switch, Non-Metallic Case, Plastic	EA	10

MODEL	PRIMARY DEPTH (INCHES)	PRIMARY WIDTH (INCHES)	PRIMARY HEIGHT (INCHES)	PRIMARY WEIGHT (LBS)
TEDS-60U	8.75	5	2.25	2.28
TDDS-30	2.5	5	7.5	2.82
TDDS-60	3	5.25	8.63	3.1
TDDS-60U	2.5	5	7.5	2.3
T750-P60NF	8.6	5.25	3	1.4